

SKYLIFT

**MINI-DERRICK
SUPER 6000**

NEW

Ph. 440-960-2100
Fax 440-960-2104
www.skyliftus.com







Climbing A Muddy Hill Using The Wireless Remote Control



**40-48 Foot Reach
Sets 55 Foot
poles**



Carrying poles



Heavy Duty Auger



fits thru 12' Gates!



**Using Job
to Handle
Transformer**



**fits on
Bucket!**

MINI-DERRICK SUPER 6000 TECHNICAL SPECIFICATIONS

BASE	High Strength Steel Construction
DRIVE	2 Speed Planetary Reduction
TRACKS	Hydraulic Extension, Rubber Construction,
ENGINE	22 H.P. Turbo Kubota Diesel
PUMP	18 G.P.M. Gear Design
HYDRAULIC TANK	21 Gallon
MAX. OPERATING PRESSURE	2900 PSI
BOOM ASSEMBLY	2 Section All Hydraulic Extension
INSULATION	48 RY Cut, CyFiberglass Boom
STABILIZERS	4 Outrigger/Hybrid Design Radial Type
ROTATOR	480 degree/High Strength Bearing
CONTROLS	Full Pressure
SHOULDER HEIGHT	40 ft./40ft.
CAPACITY	6000 lbs.
WINCH	Planetary/Plasma Rope
MATERIAL HANDLING	Integrated Red 3000 lb. Capacity
AUXILIARY POWER 1	Hydraulic Tool Circuit at Ground Plus Hose Feed
AUXILIARY POWER 2	1200 Watt/110 Volt GFI Outlet at Ground
POLE CAPBERS	Dual Sided
TRAILER	14,000 lb. GVWR Tandem Axle

MINI-DERRICK SUPER 6000 WORK LOAD CHART



OPTIONAL EQUIPMENT

- CAR HANDLER JIB/WINCH
- HYDRAULIC OVERLOAD PROTECTION
- RADIO REMOTE FOR BOTH DRIVE AND BOOM CONTROLS
- HYDRAULIC POLE GUIDES
- HYDRAULIC JIB / 2 FT. ADDITIONAL BOOM
- SINGLE MAN BASKET WITH REVERSIBLE HANGER
- TWO SINGLE MAN BASKETS WITH DUAL BUCKET HANGERS

Call for Special Requests!



3000 Leavitt Rd. Lorain, Ohio 44052
Ph. 440-960-2100 Fax 440-960-2104